

The E-25D88 Electric Power Unit utilizes a 25 hp motor which can operate two 8 gpm tool circuits at 2000 psi operating pressure.

## FEATURES:

- Flow controlled with ON/OFF valve, making operation quick and easy.
- Major components are completely accessible for convenient maintenance or repair.
- Air-to-oil cooler for hydraulic system.
- Oil reservoir at base of unit to provide stability.
- 3-phase electric motor.

## OPTIONS:

- Single-phase motor.
- Starter kit optional.



## SPECIFICATIONS

### SKID FRAME

Hydraulic System	Open Center
Length*	48 in. / 122 cm
Width*	30 in. / 76.2 cm
Height*	36 in. / 91.4 cm
Weight (dry)*	750 lbs / 340 kg
Filtration	10 Micron Return Line Canister Type
Oil Cooler	Air-to-Oil w/Independent Fan
Motor	25 HP 220V - Baldor 3-Phase - Electric
Hyd. Reservoir Capacity	19 Gallons / 72 Liters

### Hydraulic Rated Flow

A Port	8.8 gpm / 33 lpm @ 0 psi / 0 bar
	8 gpm / 30 lpm @ 2000 psi / 138 bar
B Port	8.8 gpm / 33 lpm @ 0 psi / 0 bar
	8 gpm / 30 lpm @ 2000 psi / 138 bar
Hyd. Relief Pressure	2100 psi / 138 bar

\* Approximate

ProLine Tools, LLC  
4453 W. 1730 South Bldg G  
Salt Lake City, UT 84104

801-972-3910  
801-973-7867 Fax

www.ProLineTools.com